

### DVB-T for Broadcast

- Ultra-wide dynamic range
- Protocol transparent – transmits all video, data and audio modulation formats
- Superior linear performance
- Transmission distances of >50 km
- Interfaces with M&C systems for remote monitoring
- Multiple carrier transmission



The **ViaLiteHD** DVB-T fiber optic link enables broadcast operators to transport multiple RF DVB-T feeds over optical fiber.

- Operation independent of data format
- Ultra-wide dynamic range means wireless cameras can roam freely without problems caused by signal variance
- Negligible signal degradation due to effects of noise and inter-modulation
- Inherently low phase noise
- Suitable for almost any type of analog or digital signal modulation, including FM and QPSK
- Automatic gain control mode maintains constant power output

The DVB fiber optic link system is inserted between the antenna or down-converter and the electrical receiver. The fiber is lightweight with a small diameter, and a cross-site cable can provide power to the remote end. The fiber optic transmitter can be used to power the antenna / down-converter via a voltage feed from the RF input.

#### Applications

Broadcast facilities

#### Formats

- Blue OEM
- Yellow OEM

## Technical specification

	Units	Note	DVB-T 75 ohms
Transmitter (Tx)			HRT-D6-8M-35-S1310
Receiver (Rx)			HRR-D6-8M-05
Frequency range	MHz		470-860
Impedance, RF connector			75Ω MCX
VSWR	(typ)		1:1.5
Link gain (Tx gain / Rx gain) default	dB (nom)	a	0 (-15 / +15)
Tx gain adjustment range	dB (typ)		15.5
Tx gain adjustment from default gain	dB (typ)		-8.5 to +7.0
Rx gain adjustment range	dB (typ)		15.5
Rx gain adjustment from default gain	dB (typ)		-7.5 to +8.0
Gain adjustment step size Rx and Tx	dB (typ)		0.5
Flatness, fullband	dB (max)	a d	±1.0
Flatness, fullband	dB (typ)	a d	±0.4
Gain stability over temperature, Link	dB (max)	a	±3
Gain stability	dB (typ)		0.25 @ 24 hrs
Nominal input signal / output signal	dBm		-20 / -20
IMD @ nominal output power	dB (typ)	c	-48
P1dB <sub>input</sub>	dBm (typ)	a e	2
P1dB <sub>input</sub> , at minimum Tx gain	dBm (typ)	a e	5
IP3 <sub>input</sub> , at default gain	dBm (typ)	a e	14
Noise figure, at default gain	dB (typ)	a e	23
Noise figure, at maximum Tx gain	dB (typ)	a e	17.5
Noise figure, 5 dB optical loss	dB (typ)	c e	28
SFDR	dB/Hz <sup>2/3</sup> (typ)	a	110
No damage input power	dBm		15
LNA power			Internal 12V @ 300mA
Power Consumption, Tx	W (typ)		1.9
Power Consumption, Rx	W (typ)		1.3
Optical connector			FC/APC / SC/APC
Optical wavelength	nm		1310 ± 20 (1550 ± 20 yellow OEM only)
Laser type			DFB - Distributed feedback laser
Optical power output	dBm (typ)		4.5
Summary alarm output			Open drain alarm: OPEN: Alarm, CURRENT SINK: okay
Operating temperature range			-10°C to +50°C
Storage temperature range			-40°C to +70°C
Humidity	RH		95% non-condensing humidity

- a nominal input power @ 0dB optical loss
- b nominal input power @ 1dB optical loss
- c nominal output power @ 5dB optical loss
- d default gain setting
- e Measured @ 500MHz  
All tests @ 25°C after 15 minutes warm up